

GAGE TUBING ACCESSORIES

A-200-1/
A-200-2A-201/
A-202

A-203




A-220



A-221



A-222



A-225

A-204-A/A-204-B/
A-204-C/A-204-D

A-223

A-224-A/
A-224-BA-223P-1/
A-223P-2A-210/
A-211

MODEL CHART

Model	Description
-------	-------------

Norprene® tubing is useful in a wide range of temperatures from -75 to 275°F (-60 to 135°C) and will not weaken after long term exposure to heat and ozone.

A-200-1	3/16" ID x 5/16" OD, 13 psi maximum pressure @ 73°F (90 kPa @ 23°C); 50'
A-200-2	1/4" ID x 3/8" OD, 10 psi maximum pressure @ 73°F (69 kPa @ 23°C); 50'

Rubber latex tubing has less tendency to kink in storage and occupies less space, thus is best for portable work.

A-201	3/16" ID, 9' length
A-202	3/16" ID, lengths to 50'

Clear PVC tubing is easily inspected and is therefore best for test applications where a possibility of fluid entering the tubing exists.

A-203	1/8" ID x 1/4" OD, lengths to 100'; 60 psi max. pressure @ 73°F (22°C)
-------	--

Clear flexible vinyl tubing is easily inspected, and is therefore best for test applications where a possibility of fluid entering the tubing exists.

A-220	3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 73°F (310 kPa @ 23°C)
A-221	1/8" ID x 3/16" OD, lengths to 500'; 40 psi maximum pressure @ 165°F (276 kPa @ 74°C)
A-222	.240" ID x .375" OD, lengths to 500'; 35 psi maximum pressure @ 73°F (240 kPa @ 23°C)

Flexible double column plastic tubing is used with Mark II manometers and the Wind Speed Indicator. Light gray with red color code stripe.

A-225	1/8" ID, lengths to 750'
-------	--------------------------

Flexible colored vinyl tubing is quickly distinguishable in applications where more than one line is required aiding installation.

A-204-A	3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 165°F (310 kPa @ 74°C); Opaque red
A-204-B	3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 165°F (310 kPa @ 74°C); Opaque blue
A-204-C	3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 165°F (310 kPa @ 74°C); Opaque white
A-204-D	3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 165°F (310 kPa @ 74°C); Opaque black

Black polyethylene tubing offers long life, great stability and resistance to corrosion.

A-223	1/8" ID x 1/4" OD, 10' length; 200 psi maximum @ 140°F (1379 kPa @ 60°C)
-------	--

Black nylon tubing is recommended for high temperature and pressure applications. Lengths to 1312 ft; -40 to 248°F (-40 to 120°C).

A-224-A	0.23" ID x 5/16" OD; 362 psi (2500 kPa) working pressure
A-224-B	0.256" ID x 3/8" OD, 406 psi (2800 kPa) working pressure

Black plenum fire retardant polyethylene tubing meets NFPA standard 90A for installation in air-conditioning and ventilating plenum spaces; also used in building automation systems. Lengths to 500', 100 psig maximum pressure @ 75°F (689 kPa @ 24°C).

A-223P-1	.17" ID x .25" OD
A-223P-2	1/4" ID x 3/8" OD

Aluminum tubing is recommended for permanent installations.

A-210	1/4" OD, 5' length, 500 psi maximum pressure @ 200°F (3447 kPa @ 93°C)
A-211	1/4" OD, 50' length, 500 psi maximum pressure @ 200°F (3447 kPa @ 93°C)