

# MODEL NUMBER

T D 1

Models available for quick shipment, usually within one week after factory receipt of a complete purchase order, through the Expedite Ship Plan (ESP)

### AGENCY APPROVAL

3	General Purpose, FM/CSA Explosion Proof approved
C	ATEX/IECEX Ex d + ib, Zone 0 – Flameproof

### ENCLOSURE TYPE/CONDUIT CONNECTION

0	Aluminum A356 - 3/4" NPT (dual entry)
1	Aluminum A356 - M20 (dual entry)



# MODEL NUMBER

T D 2

### POWER

7	AC Power
8	DC Power

### RELAY OUTPUT

D	DPDT Relay
H	DPDT hermetically sealed relay

### GLASS WINDOW IN ENCLOSURE

0	None
1	Window provided (not available on enclosure types 2 & 3)

### LOCATION

0	Integral
1	Remote (not available on enclosure code 4 & 5)

### AGENCY

3	General Purpose FM/CSA Class I, Division 1 & 2
7	General Purpose FM/CSA Class I, Division 2 *
C	ATEX/IECEX Ex d + ib - Zone 0 FM/CSA Class I, Division 1 & 2
G	ATEX/IECEX Ex d – Zone 1 FM/CSA Class I, Division 1 & 2

\*Use with enclosure codes 4 & 5

### ENCLOSURE TYPE/CONDUIT CONNECTION

0	Aluminum A356 – 3/4" NPT (dual entry)
1	Aluminum A356 – M20 (dual entry)
2	Cast 316 stainless steel – 3/4" NPT (dual entry)
3	Cast 316 stainless steel – M20 (dual entry)
4	304 stainless steel – 1/2" NPT* (single entry)
5	304 stainless steel – M20* (dual entry)

\*Only available with Agency code 7

